





RELEASED
05.11.27

DESIGN MB	DRAWN BY MB	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECKED 	APPROVED 	DRAWING NO. D3339	REV. B SHEET 1 OF 3
DATE 05.11.22	TITLE REPLACEMENT WEARPAD		SCALE 1:3
A	05.06.06	NEW ISSUE	
B	05.11.22	CORRECTED HOLE SPACING D3339-7F	




D3339-1F FLAT PATTERN




SECTION A-A

APPLY 7560
HARDCOAT WELD BEADS
PER DT3339-3T1
AFTER FORMING
(SEE SECTION A-A)



D3339-3 CENTER WEARPAD
(MADE FROM D3339-1F)

APPLY 7560
HARDCOAT WELD BEADS
PER DT3339-5T1
AFTER FORMING
(SEE SECTION A-A)



D3339-5 FORWARD WEARPAD
(MADE FROM D3339-1F)

D3339-1F/-3/-5 WEARPAD



NOTES:




- 1) MATERIAL: AISI 1010-1025 OR ASTM A36/A366/A1008 OR
CSA G40-21, 38W/44W/50W/60W/70W SERIES
COLD ROLLED STEEL 16 GAUGE (0.060 THICK)
- 2) PART IS SYMETRICAL ABOUT CENTER LINE
- 3) WELD PER DART QSI 004
- 4) FINISH: POWDER COAT GREY SANDTEX (REF. 4.3.5.6) PER DART QSI 005 4.3
- 5) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED
- 6) ALL DIMENSIONS ARE IN INCHES
- 7) BREAK ALL SHARP CORNERS 0.063 MAX

Copyright © 2005 by DART AEROSPACE LTD

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.

DART

DESIGN MB	DRAWN BY MB	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECKED 	APPROVED 	DRAWING NO. D3339	REV. B SHEET 2 OF 3
DATE 05.11.22	TITLE REPLACEMENT WEARPAD		SCALE 1:4



**D3339-7F FLAT PATTERN****D3339-7B LONGITUDINAL BEND****D3339-7 LONG FORWARD WEARPAD****NOTES:**



- 1) MATERIAL: AISI 1010-1025 OR ASTM A36/A366/A1008 OR CSA G40-21, 38W/44W/50W/60W/70W SERIES COLD ROLLED STEEL 16 GAUGE (0.060 THICK)
- 2) PART IS SYMMETRICAL ABOUT CENTER LINE
- 3) WELD PER DART QSI 004
- 4) FINISH: POWDER COAT GREY SANDTEX (REF. 4.3.5.6) PER DART QSI 005 4.3
- 5) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED
- 6) ALL DIMENSIONS ARE IN INCHES
- 7) BREAK ALL SHARP CORNERS 0.063 MAX

Copyright © 2005 by DART AEROSPACE LTD


THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.

DART

DESIGN MB	DRAWN BY MB	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECKED 	APPROVED 	DRAWING NO. D3339	REV. B SHEET 3 OF 3
DATE 05.11.22	TITLE REPLACEMENT WEARPAD		SCALE 1:2

**D3339-9F FLAT PATTERN****RELEASED**
05.11.27 

APPLY 7560
HARDCOAT WELD BEADS
PER DT3339-9T1
AFTER FORMING
(SEE SECTION A-A)

**D3339-9 AFT WEARPAD****NOTES:**

- 1) MATERIAL: AISI 1010-1025 OR ASTM A36/A366/A1008 OR CSA G40-21, 38W/44W/50W/60W/70W SERIES COLD ROLLED STEEL 16 GAUGE (0.060 THICK)
- 2) PART IS SYMETRICAL ABOUT CENTER LINE
- 3) WELD PER DART QSI 004
- 4) FINISH: POWDER COAT GREY SANDTEX (REF. 4.3.5.6) PER DART QSI 005 4.3
- 5) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED
- 6) ALL DIMENSIONS ARE IN INCHES
- 7) BREAK ALL SHARP CORNERS 0.063 MAX

Copyright © 2005 by DART AEROSPACE LTD

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.